



Feature:

1. The ink screen electronic conference table is an intelligent paperless conference device that transmits display information to the terminal through wireless WIFI V6 routing technology combined with a PC management system. Applicable to conference rooms of high-end hotels, government agencies, large enterprises and companies.
2. Low-carbon and environmentally friendly, simple to operate, replaces traditional paper table signs, reduces paper printing, and arranges the venue in advance. It is the best choice for the information upgrade of major conference venues.
3. Made of aluminum alloy, beautiful appearance, high-end atmosphere.
4. Compared with traditional electronic table signs, it has the characteristics of no reflection when taking photos, no glare when watching for a long time, no black screen when power off, and strong battery life.
5. The screen adopts E-Ink ink screen technology, which is easy to read, flicker-free, radiation-free, and does not hurt the eyes when watching for a long time. The reading angle can be close to 180°, and full-angle reading can bring a better reading experience.
6. Energy saving and power saving, the display is static, power off does not affect the display content, no refresh and no power consumption, extremely low power consumption, built-in six CR2450 electronics, full power is updated twice a day, can be used for 3-5 years, ultra-long standby.
7. Adopts advanced wireless WIFI 2.4G communication technology, wireless control, one-key refresh, fast and efficient, simple operation interface, no need to learn, quick to get started, wireless communication distance 25m.
8. Double-sided display (supports double-sided display), beautiful, simple and generous.
9. Web-based application interface, supports cross-platform operation.
10. Wireless communication rate 200/50kbps, custom two-way communication protocol, data software and hardware verification, safe and reliable.
11. System software supports cloud and LAN private server deployment, ① Click the link to log in to the conference table system ② Add a meeting ③ Add a conference table ④ Select a template ⑤ Modify the content directly on the page ⑥ Update the content of the conference table card (large quantities of applications can also export excel tables to modify the edited content and then import the table).

Specification:

| | |
|-------------------------|---|
| Screen size | 7.5 inches |
| Product size | 208*44*150mm (length × width × height) |
| Screen color | black, white and red three-color screen display |
| Screen resolution | 800*480 |
| Visible area | 163.20 (H) * 97.92 (V) mm |
| DPI | 124 |
| Grayscale | black, white and red 2 grayscale |
| Process | aluminum alloy metal shell/ABS |
| Display content | support name, position, meeting theme, unit, etc. |
| Working temperature | 0~40 °C |
| Storage temperature | -25~60 °C |
| Relative humidity | 5%~95% (no condensation) |
| Background template | customize various fonts and font sizes, adjust background template |
| Working voltage | 3.0V (minimum 2.2V) |
| Communication mode | 2.4G |
| Product weight | 528.9g |
| Installation mode | desktop, ready to use |
| Battery life | built-in six CR2450 electronics, fully charged and updated twice a day, can be used for 3-5 years |
| Transmission power | 5DB |
| Power supply mode | six CR2450 electronics |
| Transmission distance | radius 25M |
| Display | horizontal screen display |
| Heat dissipation method | natural air cooling |
| Structure | upright double-sided display, base local integration |
| Communication rate | 200/50Kbps |
| Receiving sensitivity | -100DB |
| Working frequency band | 2402-2483MHZ (private protocol) |
| Appearance color | silver, gray |