



### Product Features

1. Adopt U-band adjustable frequency solution to improve the flexibility of use
2. Adopt UHF high-performance integrated circuit design, stable and reliable
3. Visual high-definition screen display, which can display working frequency, channel, battery power, RF/AF signal and other contents
4. Metal hand-held texture, ergonomic design, streamlined appearance processing, better fit the hand curve, comfortable grip
5. Each channel has the function of independent manual selection of spectrum frequency points
6. One-key infrared frequency setting, multiple transmitters can be selected and interchanged, simple operation
7. Digital frequency locking technology, super anti-interference ability

### Specifications

Receiver Parameter indicators:			
RF range	640.00-690.00MHZ	Bandwidth	30MHz per channel
Modulation mode	FM frequency modulation	Frequency matching mode	Infrared automatic frequency matching
Number of channels	200 channels	Noise suppression mode	automatic noise detection and digital ID Code noise
Deviation	45KHz	Dynamic range	110dB
Frequency response	60Hz-18KHz	Antenna interface	BNC/50Ω*2
Output interface	1 unbalanced φ6.35mm interface; 2 independent balanced XLR interfaces	Power supply	DC 12V 600mA
Dimensions (length*depth*height)	420*180*45mm (excluding ear hooks and antennas)		
Transmitter Parameter indicators:			
Head	dynamic handheld	LCD display	channel, frequency, power
Oscillation mode	PLL Phase-locked loop	Output power	3dBm-10dBm (LO/H conversion)
Battery current	<100mA (HF), <80mA (LF)	Working voltage	3V (AA alkaline battery × 2)
Operating distance	about 60 meters		