



Feature:

1. Designed based on the principle of acoustic interference
2. Strong directional microphone, with windproof sponge cover, can effectively block noise
3. Excellent directivity, making it not easy to produce howling when used in sound reinforcement applications
4. Gooseneck bending adjustment structure, the microphone head can be adjusted to the appropriate position at will
5. With microphone on/off key, the speaking key and microphone rod are equipped with microphone speaking status LED indicator
6. Made of zinc alloy die-casting, it has good stability and shock resistance, and the bottom is equipped with shockproof foot pads to effectively prevent noise caused by desktop vibration
7. Support 48V phantom power supply, one-button switch microphone, convenient and atmospheric, mainly used in professional occasions such as speeches, high-end meetings, lecture halls, etc.

Specification:

Frequency response	20Hz-20KHz
Sensitivity	-33dB
Directivity	strong directivity
Output impedance	680Ω
Signal-to-noise ratio	>65 dB
Phantom power supply	48V DC
Maximum power consumption	0.4W
Color	brown, microphone rod: black
Shell material	zinc/aluminum alloy
Connector	M16 aviation female core-4Ppin*1 M16 aviation male core-4Ppin*1 XLR male socket*1
Weight	0.9kg
Dimensions (mm)	Base: 138*98*54 Microphone rod: Microphone rod: φ 21.5*294 (without windshield)