



Feature:

1. Gooseneck-free design, using FionTu's original DMA digital microphone array technology
2. Built-in 21 microphone heads, broadband pickup, long pickup distance, good directivity, excellent sound quality
3. Any unit can be flexibly configured as a chairman unit or an executive chairman unit, and there is no limit on the number of chairman units
4. The shell adopts one-piece molding and CNC machine tool precision processing technology, touch-type speaking switch, simple and convenient
5. The system has automatic repair function and supports hot plug of lines
6. According to the conference control software purchased by the user, a variety of conference management functions can be realized

Specification:

Technical parameters of the whole machine	
Pickup technology	Array microphone pickup
Number of microphone heads	21
Frequency response	30Hz-18kHz
Signal-to-noise ratio	>80 dB
Dynamic range	>95dB
Total harmonic distortion	<0.05%
Maximum power consumption	1W
Color	Black, Silver
Weight	0.6kg
Connection method	FionTu conference six-core dedicated connection cable
Shell material	Aluminum alloy
Dimensions (mm) length * width * height	284 * 57 * 48
Microphone parameters	
Pickup microphone	9.7mm diameter gold-plated capacitor
Directional characteristics	Directional broadband
Sensitivity	-38 dB
Frequency response	20Hz-20KHz
Input impedance	2.2KΩ
Maximum sound pressure level	110 dB (THD<3%)