



Feature:

1. The touch ultra-thin high-definition display screen is integrated with the lifter, with no exposed connection wires, no connection backplane, and no exposed screws, ensuring that the lifting display touch screen is beautiful and generous overall
2. With integrated lift with microphone, the microphone lift has an automatic straightening function. When the microphone stem is bent, the machine can automatically straighten the microphone stem when it is turned off, without damaging the stem
3. The equipment adopts an all-aluminum structure, high-quality aluminum materials plus CNC precision carving processing, the display screen frame and chassis are made of aluminum alloy, making the overall equipment exquisite, light, beautiful and atmospheric
4. The surface treatment of the equipment is anodized, and the color is bright
5. The thickness of the equipment panel is only 3mm, the width is only 70mm, and the space occupied is small
6. The transmission structure is specially treated to minimize the noise. The central control protocol is highly compatible and compatible with all control hosts. After the control device rises, the screen automatically powers on, and after descending, the screen automatically powers off, saving and environmental protection
7. Paperless ultra-thin capacitive LCD screen lifter, with a resolution of 1920*1080P, rear electronic table card, integrated double-sided LCD display The display effect is clear and bright, and the backlight design can be adjusted to prevent fatigue caused by excessive brightness or darkness.
8. Supports HDMI and VGA two-way signal input. When only one signal is input, the screen will automatically recognize the signal. When two signals are input at the same time, they can be manually switched through the panel buttons. When there is no signal input, the screen automatically enters power saving mode.
9. The equipment can be centrally controlled through the central control software and can be controlled by the host. One button can make all the equipment in the room rise or fall.
10. The desktop panel has a USB interface, and files can be browsed or uploaded by connecting a USB flash drive

Specification:

| | |
|--------------------------------------|--|
| Touch screen | support touch |
| Lifting time | 28S |
| Elevation angle | 0-30 °, fully in line with ergonomic principles, without blocking sight and face |
| Environmental conditions | -20°C ~ 50°C, relative humidity ≤70% |
| Screen size | 15.6 |
| Screen ratio | 16:9 |
| Screen resolution | 1920*1080 |
| Video interface | 1 VGA, 1 HDMI |
| Control interface | 2 groups of 232/485 input and output interfaces, respectively controlling the microphone and display lifting, supporting hand-in-hand connection 1 USB port for power on/off, 1 USB port for data transmission |
| Microphone connection method | FionTu conference six-core dedicated connection cable |
| Microphone rod length | 409mm |
| Backlight type | WLED, 15K hours, including LED driver |
| Contrast | 600:1 |
| Brightness | 300cd/m² |
| Viewing angle | 45/45/20/40 (Typ.) |
| Display thickness | 7.65mm |
| Power supply | AC220V50-60/HZ |
| Power consumption | 25W |
| Net weight | 13.3KG |
| Gross weight | 15.56KG |
| Panel size | 555*70*3MM (length × width × height) |
| Panel opening | 556*71*3MM (length × width × height) |
| Chassis size | 538.2*59*647 MM (length × width × height) |
| Chassis opening | 540.2*61 MM (length × width) |
| Secondary screen parameters | |
| Secondary screen size | 10.1 inches |
| Secondary screen | does not support touch |
| Secondary screen resolution | 1280*800 (10.1 inches) |
| Secondary screen contrast | 600:1 |
| Secondary screen brightness | 330 (10.1 inches) |
| Secondary screen working environment | Working temperature:0~50°C; Storage temperature: -20~60°C |
| Secondary screen viewing angle | 89/89/89/89 (Typ.) (CR≥10) |
| Secondary screen signal system | LVDS |

| | |
|----------------------------|------------|
| Microphone | |
| Frequency response | 80Hz-16KHz |
| Microphone input impedance | 1KΩ |
| Sensitivity | -46dBV/Pa |
| Maximum SPL | 125dB (A) |
| Signal-to-noise ratio | > 80dB |
| THD | < 0.1% |
| Power consumption | 3W |