



Feature:

1. The touch ultra-thin high-definition display screen is integrated with the lifter, with no exposed connection wires, no connection backplane, and no exposed screws, ensuring that the lifting display touch screen is beautiful and elegant as a whole
2. The equipment adopts an all-aluminum structure, high-quality aluminum materials plus CNC precision carving processing, the display frame and chassis are made of aluminum alloy, making the overall equipment exquisite, light, beautiful and atmospheric
3. The surface treatment of the equipment is anodized, and the color is bright
4. The thickness of the equipment panel is only 3mm, the width is only 70mm, and the space occupied is small
5. The transmission structure is specially treated to minimize the noise. The central control protocol is highly compatible and compatible with all control hosts. After the control device rises, the screen automatically powers on, and after descending, the screen automatically powers off, saving and environmental protection
6. 17.3-inch ultra-thin LCD touch screen display, with a resolution of 1920*1080P, clear and bright display effect, adjustable backlight design to prevent fatigue caused by excessive brightness or darkness
7. Supports HDMI and VGA signal input. When only one signal is input, the screen will automatically identify the signal. When two signals are input at the same time, they can be manually switched through the panel buttons. When there is no signal input, the screen automatically enters power saving mode
8. The equipment can be centrally controlled through the central control software and can be controlled by the host. One button can make all indoor equipment rise or fall
9. Built-in loop-through output power socket can supply power to the terminal to reduce the wiring of the terminal power socket, and the wiring on the project site is neater and more beautiful
10. The desktop panel has a USB interface, and files can be browsed or uploaded by connecting a USB flash drive

► Specification:

Touch screen	support touch
Lifting time	28S
Elevation angle	0-30 ° , fully in line with ergonomic principles, without blocking sight and face
Environmental conditions	-20°C ~ 50°C, relative humidity ≤70%
Screen size	17.3
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	1 VGA, 1 HDMI
Control interface	1 to control the lifting of the display screen, 1 USB interface for power on/off, 1 USB interface for data transmission
Backlight type	WLED, 15K hours, including LED driver
Contrast	600:1
Brightness	300cd/m²
Viewing angle	45/45/20/40 (Typ.)
Display thickness	7.65mm
Power supply	AC220V50-60/HZ
Power consumption	45W
Net weight	9.42KG
Gross weight	11.8KG
Panel size	476*70*3MM(length × width × height)
Panel opening	477*71*3MM (length × width × height)
Chassis size	459.2*59*562MM (length × width × height)
Chassis opening	461.2*61MM (length × width)