



Feature:

1. The touch ultra-thin high-definition display screen is integrated with the lifter, with no exposed connection wires, no connection backplane, and no exposed screws, ensuring that the lifting display touch screen is beautiful and elegant as a whole
2. The equipment adopts an all-aluminum structure, high-quality aluminum materials plus CNC precision carving processing, the display frame and chassis are made of aluminum alloy, making the overall equipment exquisite, light, beautiful and atmospheric
3. The surface treatment of the equipment is anodized, and the color is bright
4. The thickness of the equipment panel is only 3mm, the width is only 70mm, and the space occupied is small
5. The transmission structure is specially treated to minimize the noise. The central control protocol is highly compatible and compatible with all control hosts. After the control device rises, the screen automatically powers on, and after it falls, the screen automatically powers off, saving and environmental protection
6. Paperless ultra-thin capacitive LCD screen lifter, with a resolution of 1920*1080P, rear electronic table card, integrated double-sided LCD display, clear and bright display effect, adjustable backlight design to prevent fatigue caused by excessive brightness or darkness
7. Supports HDMI and VGA signal input. When only one signal is input, the screen will automatically identify the signal. When two signals are input at the same time, they can be manually switched through the panel buttons. When there is no signal input, the screen automatically enters power saving mode
8. The equipment can be centrally controlled through the central control software and can be controlled by the host. One button can make all the equipment in the room rise or fall
9. The desktop panel has a USB interface. You can browse or upload files by connecting a USB flash drive

► Specification:

Touch screen	support touch
Lifting time	28S
Elevation angle	0-30°, fully in line with ergonomic principles, and does not block sight and face
Environmental conditions	-20°C ~ 50°C, relative humidity ≤70%
Screen size	18.4
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	1 VGA, 1 HDMI
Control interface	1 control display screen lifting, 1 USB port for power on/off, 1 USB port for data transmission
Backlight type	WLED, 15K hours, including LED driver
Contrast	600:1
Brightness	300cd/m²
Viewing angle	45/45/20/40 (Typ.)
Display thickness	11.8mm
Power supply	AC220V50-60/HZ
Power consumption	55W
Back screen size	10.1 inches
Net weight	12.5KG
Gross weight	15.1KG
Secondary screen size	10.1 inches
Secondary screen	does not support touch
Secondary screen resolution	1280*800 (10.1 inches)
Secondary screen contrast	600:1
Secondary screen brightness	330 (10.1 inches)
Secondary screen working environment	Working temperature: 0~50°C Storage temperature: -20~60°C
Secondary screen viewing angle	89/89/89/89 (Typ.) (CR≥10)
Secondary screen signal system	LVDS
Panel size	510*77*3 MM (length × width × height)
Panel opening	511*78*3 MM (length × width × height)
Chassis size	487.6*66*647 MM (length × width × height)
Chassis opening	489.6*68 MM(length × width)