



Feature:

1. The display screen and the lifter are integrated with each other, without exposed connecting wires, connecting back panels, or exposed screws, ensuring that the lifting display touch screen is beautiful and elegant overall
2. The equipment adopts an all-aluminum structure, high-quality aluminum materials plus CNC precision carving, and the display screen frame and chassis are made of aluminum alloy, making the overall equipment exquisite, light, beautiful, and atmospheric
3. The surface treatment of the equipment is anodized, and the color is bright
4. The transmission structure is specially treated to minimize noise. The central control protocol has strong compatibility and is compatible with all control hosts. After the control device rises, the screen automatically powers on, and after it falls, the screen automatically powers off, saving the environment
5. 23.8-inch touch screen display, with a resolution of 1920*1080P, the display effect is clear and bright, and the backlight design can be adjusted to prevent fatigue caused by excessive brightness or darkness
6. Supports HDMI and VGA two-way signal input. When only one signal is input, the screen will automatically recognize the signal. When two signals are input at the same time, they can be manually switched through the panel buttons. When there is no signal input, the screen automatically enters power saving mode
7. The equipment can be centrally controlled through the central control software and can be controlled through the host. One button can make all the indoor equipment rise or fall
8. The built-in loop-through output power socket can supply power to the terminal to reduce the wiring of the terminal power socket, and the wiring on the project site is more neat and beautiful
9. The desktop panel has a USB interface, and you can browse or upload files by connecting a USB flash drive

► Specification:

Touch screen	support touch
Lifting time	28S
Elevation angle	0-30°, fully in line with ergonomic principles, and does not block sight and face
Environmental conditions	-20°C ~ 50°C, relative humidity ≤70%
Screen size	23.8
Screen ratio	16:9
Screen resolution	1920*1080
Video interface	1 VGA, 1 HDMI
Control interface	1 control display lifting , 1 USB port for power on/off, 1 USB port for data transmission
Backlight type	WLED, 15K hours, including LED driver
Contrast	600:1
Brightness	300cd/m²
Viewing angle	45/45/20/40 (Typ.)
Display thickness	19.55mm
Power supply	AC220V50-60/HZ
Power consumption	70W
Panel size	648*77*3 MM(length × width × height)
Panel opening	649*78*3 MM(length × width × height)
Chassis size	623.2*66*687 MM (length × width × height)
Chassis opening	625.2*68 MM (length × width)