



► Specification:

8Ω/Stereo	4 × 250W
4Ω/Stereo	4 × 425W
2Ω/Stereo	4 × 720W
16Ω/Bridge	2 × 500W
8Ω/Bridge	2 × 850W
4Ω/Bridge	2 × 1440W
RMS Output Voltage (THD = 1%, 1kHz)	44.7V
Input Sensitivity	Selectable: 35dB, 32dB, 29dB, 26dB
THD+N	Typical: 0.01% (10% rated output power, 1kHz, 8Ω)
Crosstalk Suppression	≥90dB (below rated power, 20Hz-1kHz, 8Ω)
Frequency Response Typical values	+0dB, -0.5dB (10% rated output power, 20Hz-20kHz, 8Ω)
Input impedance	20kΩ (balanced), 10kΩ (unbalanced)
Damping factor	Typical value: 3500 (8Ω, 20Hz-200Hz)
Signal-to-noise ratio	≥100dB (A-weighted, 20Hz-20kHz, 8Ω)
Power supply requirements	90~260VAC, 50/60Hz
Protection functions	Power undervoltage protection, amplifier output DC protection, overheating protection, temperature-dependent power control, overload power control
Dimensions	483×45×370 (W×H×D)
Net weight	9kg
Static power consumption	40W
Dynamic power consumption	213.6W