



► Feature:

1. Wall-mounted design, private mold white alloy plastic injection molding, beautiful craftsmanship
2. The terminal adopts embedded technology and DSP audio processing technology
3. Adopting high-speed industrial-grade chips, the startup time is less than 1s
4. Built-in 2×25W fixed resistance output Class D amplifier module, beautiful sound and strong power
5. Built-in network hardware audio decoding module, supporting TCP/IP, UDP, IGMP (multicast. protocols
6. Realize network transmission of 16-bit stereo CD-quality audio signals
7. Stereo audio output, can be connected to an external power amplifier or active speakers
8. 1 stereo line input, 1 microphone input, with independent volume adjustment switch
9. 1 USB input interface, can realize local USB playback function
10. Built-in analog audio signal backup module, support constant voltage 70V/100V signal input
11. When the device detects that there is no network signal input or power failure, it automatically switches to input constant voltage signal amplification to achieve dual line redundancy
12. 1 short-circuit signal input, which can be connected to the linkage trigger signal, and can trigger the terminal alarm in an emergency
13. 1 short-distance signal output, which can be linked to trigger other devices in an emergency
14. Support intelligent voice prompt function when registering new terminal configuration (if the device is connected.
15. With 1000-level custom audio priority silent control function
16. With server unified authorization operation management function, unified configuration management user and password
17. With digital audio time-lapse breakpoint playback function to ensure broadcast synchronization effect
18. With PSTN telephone broadcast, support SMS voice broadcast function
19. With mobile phone WIFI on-demand, support wireless remote control on-demand function
20. Support DHCP, compatible with routers, switches, bridge gateways, Modem, Internet, 2G, 3G, 4G, multicast, unicast and other network structures

► Specification:

Network interface	standard RJ45 input
Support protocols	TCP/IP, UDP, IGMP (multicast)
Audio format	MP3/MP2
Output power	2×25W fixed resistance
Frequency response	50Hz~18KHz
Sampling rate	8K ~ 48KHz
Transmission rate	100Mbps
Audio mode	16-bit stereo CD quality
Harmonic distortion	≤0.3%
Signal-to-noise ratio	> 70dB
Audio source output level	1000mV industrial standard crimping terminal
Audio source output impedance	470Ω
Ambient temperature	5°C ~ 40°C
Ambient humidity	20% ~ 80% relative humidity
Power consumption	≤36W
Input power	~220V 50Hz
Dimensions	220×160×43mm
Weight	1.28Kg