



Feature:

1. Double-sided board + SMT surface mount technology, Omron relay (can bear 60A surge current impact), copper output universal socket, ensure the product's ultra-high quality.
2. 12-way power sequence control, each delay 1 second, can be set by software to delay 5 minutes to shut down, providing better protection for the projector.
3. The whole machine capacity is 63A, equipped with Delixi bipolar 63A circuit breaker.
4. A total of 12+1 socket outputs are provided, of which one panel is always connected, and the rear panel 6 outputs have power purification function.
5. Support 2 machines cascade.
6. MCU control intelligent design, with standard RS232 (RS232 control can be upgraded to RS485 control) serial port control function, can set 255 ID addresses, can support up to 255 units at the same time, suitable for large-scale centralized control.
7. With external level (5V-12V) control interface (external level control interface can be changed to external switch control), and cascade control port.
8. With digital LED voltage indication.
9. With bypass function to prevent emergency use in case of internal failure.
10. Each output can be controlled separately, and the switch can be locked to avoid misoperation.

Specification:

Power supply	AC220V/50Hz
Total capacity	FTxiFTI 63A
Panel control	timing control switch
Weight	5KG
Dimensions	482x280x88 (w*d*h/mm)
Front panel	single-phase three-wire 10A universal socket
External control	standard RS232 serial port control
Baud rate	2400
Voltage signal control	DC5~12V