



## Specification:

| Specification                         | Details   |
|---------------------------------------|---|
| Maximum Stable Communication Distance | 100 meters  |
| Maximum Capacity of Main Control Unit | 1500 voting devices   |
| PC Communication Indicator            | Yes   |
| Hot Backup Indicator                  | Yes   |
| Base Station Communication Indicators | 8 groups  |
| Hot Backup Safety Features            | Main communication port, backup communication port, and conference signal testing port; automatic switch to backup port if the main port fails. |
| Signal Detection                      | Real-time detection of wireless signals before, during, and after the conference.   |
| Communication Port Interface          | RJ45  |
| Operating Temperature Range           | -20°C to +50°C  |
| Power Supply                          | AC 220V-230V, 50Hz-60Hz   |
| Maximum Number of Base Stations       | 8   |

|   |                      |
|---|----------------------|
| <b>Maximum Number of Voting Devices</b>       | 1500                 |
| <b>Communication Speed with Host</b>          | 115200bps            |
| <b>Communication Speed with Base Stations</b> | 1M bps               |
| <b>Interface</b>                              | RJ45                 |
| <b>Power Consumption</b>                      | 2W                   |
| <b>Dimensions</b>                             | 480mm x 355mm x 88mm |
| <b>Weight</b>                                 | 5.8 kg               |