



### Feature:

1. Top-grade gold film high-fidelity microphone capsule, super directional sound collection effect, better sound quality
2. Built-in high-performance CPU, faster processing speed, better sound quality
3. Effective sound collection angle of 100° can prevent interference from adjacent microphones and suppress howling
4. With video switcher and camera, after using computer preset, the camera automatic tracking function can be realized
5. Customized chairman unit configuration function, any unit can be temporarily defined as chairman unit according to on-site needs, and there is no limit on the number of chairman units
6. The system has automatic repair function and supports hot plugging of lines
7. The microphone can be adjusted from -50° to 45° (horizontal)
8. Made of zinc/aluminum alloy, anodized process, CNC precision processing high-gloss edge, novel appearance, mainly used in high-end conferences and other professional occasions

### Specification:

Output frequency response	40Hz-16KHz
Signal-to-noise ratio	> 74 dB
Dynamic range	> 108 dB(1 KHz)
Total harmonic distortion	< 0.05%
Maximum power consumption	1.5W
Phantom power	48V DC
Headphone volume	10mW
Headphone load	> 16 Ω
Headphone output interface	Ø 3.5 mm stereo jack
Shell material	Zinc/aluminum alloy
Connection method	FionTu conference six-core dedicated connection cable
Weight	0.9kg
Color	dark blue
Dimensions (mm) length*width*height	Microphone rod:200*34.5*23, base:138*98*54
Microphone parameters	
Pickup microphone	14mm diameter gold-plated condenser microphone
Directional characteristics	Supercardioid
Sensitivity	-28 dB
Frequency response	30Hz-18KHz
Input impedance	2.2KΩ
Maximum sound pressure level	130 dB (THD<3%)
Equivalent noise	25 dB-A