



## Feature:

1. Adopting the dual backup design concept, it has a hand-in-hand conference system and a phantom powered microphone dual system. The two links work independently to ensure the high reliability of the system
2. Built-in high-performance CPU, faster processing speed and better sound quality
3. Customized chairman unit configuration function, you can temporarily define any unit as a chairman unit according to the needs of the site, and there is no limit on the number of chairman units
4. With the video switcher and camera, the camera can be automatically tracked after using the computer preset
5. The microphone can be adjusted from -50° to 45° (horizontal)
6. Exquisite and elegant tabletop structure, ergonomic, very modern
7. Made of zinc/aluminum alloy, anodized process, CNC precision processing high gloss edge, novel appearance, mainly used in high-end conferences and other professional occasions

## Specification:

Output frequency response	40Hz-16KHz
Signal-to-noise ratio	> 74 dB
Dynamic range	> 108 dB(1 KHz)
Total harmonic distortion	<0.05%
Maximum power consumption	1.8W
Phantom power	48V DC
Headphone volume	10mW
Headphone load	> 16 $\Omega$
Headphone output interface	Ø 3.5 mm stereo jack
Shell material	Zinc/aluminum alloy
Weight	1kg
Color	Qiang blue
Connection method	FionTu conference six-core dedicated connection cable Audio cable-2 core with shielding
Dimensions (mm) length*width*height	Microphone rod:200*34.5*23, base:138*98*54
Microphone parameters	
Pickup microphone	14mm diameter gold-plated capacitor microphone * 2
Directional characteristics	Supercardioid
Sensitivity	-28 dB
Frequency response	30Hz-18KHz
Input impedance	2.2K $\Omega$
Maximum sound pressure level	130 dB (THD<3%)
Equivalent noise	25 dB-A