



### Feature:

- Embedded unit design.
- Equipped with a 2.23-inch display screen to show volume, microphone status, sign-in, voting, and other information.
- Supports multiple voting functions, including approve, oppose, abstain, one-out-of-five selection, and three-out-of-five selection.
- Detachable base and microphone stem for an elegant and aesthetic design.
- Uses a supercardioid condenser microphone.
- Unique audio processing circuit enhances system voice clarity.
- "T" type cable connection for stability and easy installation.
- Powered by the central processor unit with DC 24V safe voltage.
- Designed to resist mobile phone and RF interference, meeting modern conference requirements.
- Chairman unit features a priority button to control the speaking order.

### Specification:

Parameter	Specification
<b>Operating Voltage</b>	DC 24V
<b>Pickup Pattern</b>	Unidirectional
<b>Signal-to-Noise Ratio (SNR)</b>	68dB
<b>Static Current</b>	42mA
<b>Sensitivity</b>	-47±1dB
<b>Cable Connection</b>	RJ45 network cable

<b>Operating Temperature &amp; Humidity</b>	-9°C to 40°C, 30%-90% RH
<b>Storage Temperature &amp; Humidity</b>	-20°C to 60°C, 10%-95% RH
<b>Installation Method</b>	Embedded installation
<b>Microphone Stem Length</b>	36cm
<b>Unit Color</b>	Classic Black
<b>Gooseneck Microphone</b>	High-directivity back-electret condenser microphone with red indicator ring