



Feature:

1. Uses 1U standard chassis; supports 2.3 million pixels, 6 Gigabit Ethernet ports to connect to LED display screen
2. Maximum width 4096 pixels, or maximum 1536 pixels
3. Supports 1 HDMI input and HDMI output, maximum 1920x1200@60Hz
4. Chipset uses dual-core processor / quad-core GPU / 1G DDR3 high-speed memory
5. 8GB built-in storage (4G available for programs).
6. Supports 2-way USB2.0, which can be used to update programs with a USB flash drive
7. Supports 1-way 3.5mm audio port, outputs HIFI stereo
8. Supports 2-way brightness sensor interface, supports automatic brightness adjustment, and timing settings
9. Supports 1080P high-definition video decoding and playback
10. Supports cloud-based hierarchical management and multi-role program publishing
11. Supports LAN encryption/USB encryption, and secure management terminal
12. Supports multi-screen NTP time synchronization and playback, without the need for a synchronization module
13. Supports LAN command scheduling, scheduled execution of sleep/wake-up/brightness, etc.
14. Supports program scheduling, multi-program sequential playback, timing settings, etc.
15. Supports program discount function within 8192 pixels (picture/text).
16. Supports multi-window display playback and arbitrary overlay, and can freely set window size and position
17. Supports playback of various program materials, such as pictures, videos, text, tables, clocks, etc. Video formats support AVI, WMV, MPG, RM/RMVB, MOV, DAT, VOB, MP4, FLV; audio formats support MPEG-1 Layer III, AAC; image formats support bmp, jpg, png, gif, etc
18. Supports control on different platforms such as Windows PC, web, Android/Hongmeng/IOS mobile. Windows PC: LEDVISION/PlayerMaster. Web: Browser. Mobile APP control: LED Wizard
19. Support 100M LAN port, can be connected to wired network, support DHCP mode and static mode
20. Support Wi-Fi 2.4G band, Wi-Fi hotspot mode or Wi-Fi client mode
21. Support 4G card communication, support 4G network (optional)
22. Support GPS positioning (optional)
23. Power supply voltage supports AC100~240V, 50/60Hz