



### Product Features

1. The overall high-end and solemn, beautiful appearance design, in line with modern aesthetic standards
2. Professional high-fidelity capacitor 14mm microphone core, sensitive sound pickup, clear voice
3. Anti-interference circuit design, can prevent interference from mobile phones and other electronic products
4. The microphone has a speaking indicator light, which shows the unit speaking or off status
5. The unit is a passive device, powered by the system host, the voltage is DC24V, which is within the safe range
6. 2.4-inch TFT color LCD display can display ID addressing number, time, speaking timer and other information
7. The chairman unit can be installed arbitrarily without position restrictions when connected, and has the priority function of fully controlling the order of the meeting
8. Hand-in-hand connection mode, easy to install and maintain

### Specifications

Frequency response	20Hz-20KHz	Total harmonic distortion	<0.05%
Sensitivity	-46 dBV/Pa	Signal-to-noise ratio	>80dB
Equivalent noise	20 dBA (SPL)	Maximum sound pressure level	125 dB (THD<5%)
Input impedance	2 kΩ	Directivity	cardioid
Base size	100 width × 134 depth × 57 height mm (excluding the shaft)		
Microphone rod size	220 length × 33 width × 25 height mm		
Output wiring	comes with 1.1-meter eight-core female outlet		
Display	2.4-inch TFT color display; resolution 240x320		