



Product Features

1. Adopting digital technology as the core, built-in high-performance CPU, 32-bit high-speed floating-point DSP processing to achieve perfect and clear sound quality
2. Powered by high-performance switching power supply to reduce the impact of long-distance transmission on sound quality
3. Anti-interference circuit design to prevent interference from mobile phone signals
4. Built-in 2.8-inch color display, which can display the number of chairmen, representatives, speakers, conference mode, date, time, etc
5. Support menu settings: conference settings, speaking time settings, volume settings, automatic addressing, system settings, etc., realize conference function control through 6 function buttons
6. Support first-in-first-out, last-in-first-out
7. Support 1-12 speakers, support mute and close priority mode
8. Support limited speaking time setting, maximum setting is 3 minutes; support timed closing time setting, maximum setting is 99 minutes
9. Support linear input and output volume, balanced and unbalanced output volume setting
10. Support re-addressing and adding new units
11. Support three voice options: Chinese, Traditional, and English
12. Support voice-activated microphone opening function, the maximum number of chairpersons can reach 12
13. Support camera tracking function, optional pelco-D, pelco-P, sony_d70 and other camera control protocols
14. Support wired conference camera control software to set camera tracking function
15. Multi-channel audio input and output interface, can be connected to sound reinforcement or recording equipment
16. With central control RS-232 interface, can be connected to the central control system

Specifications

Frequency response	20Hz-20kHz	Signal-to-noise ratio	>96dBA
Total harmonic distortion	≤0.05%	Host power supply	AC220V/50Hz
Central control connection port	RS-23 2 serial ports × 1	TEL output	RCA (lotus socket) × 1
Software control interface	PC-USB × 1	Line input	RCA (lotus socket) × 1
Line output	RCA (lotus socket) × 1	TEL input	RCA (lotus socket) × 1
Host size	480 length × 260 depth × 93 height mm (including foot pads)		
Microphone unit interface	round head DIN-8 socket interface × 4; RJ45 network cable interface × 4		
Camera interface	RS-232 small serial port × 1; RS-422 serial port × 1		
Output interface	balanced XLR cannon socket × 1; unbalanced 6.35 socket × 1		