



► Product Features

1. Adopt FionTu's original digital conference technology, all conference functions can be centrally controlled through the panel navigation keyboard
2. Adopt high-speed RISC embedded digital processing hardware architecture to make the system operation speed and stability reach an unprecedented level
3. Full digital audio processing technology, all channels of sound are processed with CD quality, effectively preventing feedback and interference
4. The conference system ensures the privacy and security of the meeting
5. The TCP/IP Ethernet protocol is used between the PC and the host, and the host and the unit are connected by a dedicated 6-core cable, and the hand-in-hand connection is adopted
6. Built-in video tracking function, up to 6 high-speed PTZ cameras can be configured; the speaking unit can be video tracked after preset
7. With 232 central control interface protocol, it can expand any central control system on the market for venue control management, conference speech control, etc
8. Multiple microphone management modes: first-in-first-out, voice control mode, and restriction mode. The number of speakers can be customized from 1 to 8
9. 4-channel unit input port, 2-channel XLR audio output interface, 2-channel Phoenix terminal audio output interface, making the system expansion more flexible
10. The system has an automatic repair function and supports "hot plugging" of lines

► Specifications

Microphone capacity	<150	Frequency response	30Hz-20KHz
Signal-to-noise ratio	>82 dB(A)	Dynamic range	>90 dB
Channel isolation	>86 dB	Total harmonic distortion	<0.05%
Main power supply	AC100-240V 5A 50 - 60Hz	Audio input	775mV balanced
Control interface	RS232/RS485/ RJ45 network port	Output load	>1KΩ
Maximum power consumption	150 W	Audio input interface	XLR *1
Audio output interface	XLR *2; Phoenix terminal *2	Audio output	1V balanced
Unit interface	large six-core DIN *4	Color	black
Host size length * width * height	483 * 360 * 100.5mm	Weight	5.26kg