



► Product Features

1. Square pole microphone design, high sensitivity, high-end and solemn appearance
2. Digital audio transmission technology, realizes audio signal transmission and processing, and resists mobile phone, electromagnetic and high-frequency interference
3. The microphone and the host are connected in a 6-core T-type cable "hand in hand" manner, and the unit comes with a tail line, which can effectively prevent the plug from falling off
4. Adopts gold-plated film high-fidelity microphone sound head, cardioid directional sound reception effect, and better sound quality
5. The microphone has a red indicator light to display the working status of the unit, speaking/off
6. Customized chairman machine configuration function, according to on-site needs, any unit can be customized as a chairman unit, and there is no limit on the number of chairman units
7. With voice control function, the microphone can be automatically turned on after speaking
8. The unit is uniformly powered by the host and supports hot plugging of microphones

► Specifications

Weight	710g	Frequency response	60Hz~16KHz
Input impedance	1KΩ	Dynamic range	>103 dB (1KHz)
Sensitivity	-35dBV/Pa	Signal-to-noise ratio	>70dB
THD	<0.1%	Maximum power consumption	1.5W
Type	cardioid directional		
Dimensions (mm) length * width * height	microphone rod 209x32x71; base 138x98x55		
Connection method	conference six-core dedicated connection line		