



Product Features

1. Adopting digital technology as the core, built-in high-performance CPU, 32-bit high-speed floating-point DSP processing to achieve perfect and clear sound quality
2. Powered by high-performance switching power supply to reduce the impact of long-distance transmission on sound quality
3. Anti-interference circuit design to prevent interference from mobile phone signals
4. Built-in 2.8-inch color display, which can display the number of chairmen, representatives, speakers, conference mode, date, time, etc
5. Support menu settings: conference settings, speaking time settings, volume settings, automatic addressing, system settings, etc., realize conference function control through 6 function buttons
6. Support first-in-first-out, last-in-first-out
7. Support 1-12 speakers, support mute and close priority mode
8. Support limited speaking time setting, maximum setting is 3 minutes; support timed closing time setting, maximum setting is 99 minutes
9. Support linear input and output volume, balanced and unbalanced output volume setting
10. Support re-addressing and adding new units
11. Support three voice options: Chinese, Traditional, and English
12. Support voice-activated microphone opening function, the maximum number of chairpersons can reach 12
13. Support camera tracking function, optional pelco-D, pelco-P, sony_d70 and other camera control protocols
14. Support wired conference camera control software to set camera tracking function
15. Multi-channel audio input and output interface, can be connected to sound reinforcement or recording equipment
16. With central control RS-232 interface, can be connected to the central control system

Specifications

| | | | |
|---------------------------------|---|-----------------------|------------------------|
| Frequency response | 20Hz-20kHz | Signal-to-noise ratio | >96dBA |
| Total harmonic distortion | ≤0.05% | Host power supply | AC220V/50Hz |
| Central control connection port | RS-232 serial ports × 1 | TEL output | RCA (lotus socket) × 1 |
| Software control interface | PC-USB × 1 | Line input | RCA (lotus socket) × 1 |
| Line output | RCA (lotus socket) × 1 | TEL input | RCA (lotus socket) × 1 |
| Camera interface | RS-232 small serial port × 1; RS-422 serial port × 1 | | |
| Output interface | balanced XLR cannon socket × 1; unbalanced 6.35 socket × 1 | | |
| Host size | 480 length × 260 depth × 93 height mm (including foot pads) | | |
| Microphone unit interface | round head DIN-8 socket interface × 4; RJ45 network cable interface × 4 | | |