



### Product Features

1. The overall high-end and solemn appearance, beautiful appearance design, in line with modern aesthetic standards
2. Professional high-fidelity capacitor 14mm microphone core, sensitive sound pickup, clear voice
3. Anti-interference circuit design, can prevent interference from mobile phones and other electronic products
4. The microphone stem has a speaking indicator light (no light when not speaking, red when speaking, indicating the speaking or off status of the unit)
5. The speaking button has an indicator light, which is always blue when speaking and always red when not speaking
6. The unit is a passive device, powered by the system host, the voltage is DC24V, which is within the safe range
7. The 2.4-inch TFT color LCD display can display representative identity, ID addressing number, time, speaking timing and other information
8. Hand-in-hand connection mode, easy to install and maintain

### Specifications

Frequency response	20Hz-20KHz	Total harmonic distortion	<0.05%
Sensitivity	-46 dBV/Pa	Signal-to-noise ratio	>80dB
Channel crosstalk	>80dB	Equivalent noise	20 dBA (SPL)
Maximum sound pressure level	125 dB (THD<3%)	Input impedance	2 kΩ
Directivity	cardioid		
Mic rod size	360 length mm; Mic head diameter 26 mm		
Display	2.4-inch TFT color display; resolution 240x320		
Output wiring	comes with 1.1-meter eight-core female outlet		
Base size	100 width × 134 depth × 57 height mm		