

T3-ZW21C



Product Features

- 1. 2.4-inch TFT color LCD display, which can display channel, power, chairman identity, address ID number, speech timer and other contents
- 2. The unit uses 3600mAH lithium-ion battery, ultra-low power consumption, can work continuously for 8 hours, and the standby time can reach 12 hours
- 3. Long press the speech button to enter the unit settings, and modify the unit's channel, address ID number and other settings
- 4. Humanized function, high-definition voice restoration, unique battery life power supply, and reject interference
- 5. Microphone rod with indicator light (no light when not speaking, bright red when speaking, speech button (no light when not speaking, bright red when speaking
- 6. Built-in Type-C charger Electrical interface
- 7. Chairman unit has priority control function

Specifications

Carrier frequency band	UHF640MHz-690MHz	Maximum deviation	±45KHz
Harmonic radiation	<-65dBm	Bandwidth	50MHz
Battery used	3600mAH lithium-ion battery	Current consumption	<200mA
Microphone rod size	360mm long, microphone head diameter 26mm		
Base size	100mm wide*134mm deep*57mm high		
Oscillation mode	PLL phase-locked frequency synthesis		
Microphone core	14mm capacitive microphone core, cardioid directivity		

www.fiontuav.com.en info@fiontu.com