



Feature:

Category	Specification
Model Number	3X, 10X
Sensor	1/2.9" SONY CMOS
Effective Pixel	2.1 Megapixel
Minimum Scene Illumination	0.1Lux at F1.6
Image Sensor White Balance	MANUAL/AUTO/ATW/INDOOR/OUTDOOR
Gain Control	AUTO
Back-light Compensation	Support
S/N Ratio	>50db
IRIS	F1.7-F3.0 (3X Model), F1.6-F2.5 (10X Model)
Focus Zoom	f=3.3mm-10mm (3X Optical Zoom), f=4.7-47mm (10X Optical Zoom)
Field of View	84 degree (3X Model), 54 degree (10X Model)
Lens	3X Optical Zoom, 10X Optical Zoom
Video Output	USB 2.0 Type B
Video Format	MJPEG: 1080P30/25, 720P30/25, 640x480, 640x360
Audio Pickup	Built-in array microphones with pickup distance of 5-8 meters
Protocol	VISCA, PELCO-D, UVC
Baud Rate	9600/38400bps
Patrol Tours	4
Preset	64
OSD Menu	LENS OSD/DOME OSD
Speed Matching Function	Support
Image Auto Flip	Support Flip/Mirror
Pan Speed	0-40 degrees/s
Tilt Speed	0-40 degrees/s

Pan Rotation Angle	0-150 degree
Tilt Rotation Angle	+30° to -30°
Auto Pan Scan	Support
Remote Control	IR Wireless remote control P/T/Z
Power	USB 2.0 Power supply
Operating Temperature	0°C ~ 50°C
Environmental Humidity	0-95% RH (non-condensation)
Dimensions (L x W x H)	350mm x 112mm x 139mm
Weight	785g
PTZ Control Protocol	VISCA, PELCO-D