



► Feature:

- Dual Analog Backup
- Low Impedance Balanced Audio Output
- Microphone Powered by 48V Pre-Amplifier
- Effective Pickup Angle of 100° to prevent interference from nearby microphones and suppress feedback.
- High-Sensitivity Gold-Plated 14mm High-Fidelity Microphone Head, ultra-directional pickup effect, with a long pickup range.
- Adjustable Microphone Stand: The stand is adjustable both front and back to meet the needs of users of different heights.
- Aluminum Alloy Material with Anodized Process: Innovative design with ergonomic structure, modern aesthetic, suitable for high-end meetings, conference halls, and other professional settings.

Specification:

Category	Specification
Microphone Pickup Head	14mm diameter gold-plated condenser microphone head (x2)
Output Frequency Response	20Hz - 20KHz
Polar Pattern	Supercardioid
Sensitivity	-28 dB
Output Impedance	<200Ω
Maximum Sound Pressure Level	130 dB (THD < 3%)
Signal-to-Noise Ratio	>76 dB
Total Harmonic Distortion	<0.05%
Equivalent Noise	25 dB-A
Dynamic Range	>110 dB (1 KHz)
Phantom Power	48V DC
Maximum Power Consumption	0.6W
Housing Material	Aluminum Alloy
Connection Method	Audio Cable - 2-core with Shielding
Weight	25kg
Color	Base: Qiang color, Microphone Rod: Black (Customizable in silver)
Dimensions (L x W x H)	Microphone Rod: 250 x 38 x 27 mm, Base: 260 x 260 mm, Height: 1500 mm
Recommended User Height	145-200 cm