



Specification:

Lamp beads	SMD/2525
Scanning method	6S
Pixel pitch	6.667mm
Pixel structure	1R1G1B
Pixel density	22500/m ²
Module resolution	48 (W) * 24 (H)
Module size	320 * 160
Main parameters	
Visible viewing distance	≥3m
Horizontal viewing angle	≥160°Vertical viewing angle: ≥160°
Color temperature	1000K-10000K adjustable
Whole screen flatness	≤0.2mm
Yes	Single point brightness and color correction
Brightness uniformity	≥97%
White balance brightness	≥5000cd/m ²
Design	De-blanking drive protection circuit and high grayscale high refresh design
Contrast	≥5000:1
Refresh rate	≥3840Hz
Frame change frequency	≥60HZ
Grayscale level	65536
Driving mode	constant current
Control mode	synchronous
Control distance	network cable: 100 meters, optical fiber: 10 kilometers
Signal interface	RJ45 interface
Brightness adjustment range	0 to 100 stepless adjustment
Continuous working time	≥72 hours
Typical life span	100,000 hours
Protection level	IP65
Installation method	magnetic fixed installation, post-maintenance Protection

Electrical parameters	
Working voltage	DC: 4.2-5V
Power supply requirements	AC: 220×(1±10%)V, 50×(1±5%)Hz
Maximum power consumption	≤800W/m ²
Average power consumption	≤350W/m ²
Environmental parameters	
Storage temperature range	-20°C to 60°C
Working temperature range	-20°C to 45°C
Working humidity range	10%-80%RH without condensation