



Specification:

Lamp beads	SMD/2020
Scanning method	32S
Pixel pitch	3.0mm
Pixel structure	1R1G1B
Pixel density	111111/m ²
Module resolution	64 (W) * 64 (H)
Module size	192mm * 192mm
Module display	Front-side GOB Process Treatment
Main parameters	
Visible viewing distance	≥3m
Horizontal viewing angle	≥160° vertical viewing angle: ≥160°
Color temperature	1000K-10000K adjustable
Flatness of the entire screen	≤0.2mm
Yes	Single point brightness and color correction
Brightness uniformity	≥99%
White balance brightness	≥570cd/m ²
Design	De-blanking drive protection circuit and high grayscale high refresh design
Contrast	≥10000:1
Refresh rate	≥1920Hz
Frame change frequency	≥ 60HZ
Grayscale level	65536
Driving mode	constant current
Control mode	synchronous
Control distance	network cable: 100 meters, optical fiber: 10 kilometers
Signal interface	RJ45 interface
Brightness adjustment range	0 to 100 stepless adjustment
Continuous working time	≥72 hours
Typical lifespan	100,000 hours
Protection level	IP5X
Installation specifications	magnetic Suction installation
Electrical parameters	
Working voltage	DC: 4.2-5V
Power supply requirements	AC: 220×(1±10%)V, 50×(1±5%)Hz

Maximum power consumption	≤539W/m ²
Average power consumption	≤180W/m ²
Environmental parameters	
Storage temperature range	-20°C to 60°C
Working temperature range	-20°C to 50°C
Working humidity range	10%-80%RH without condensation