

## Active wall-mounted speakers FP10-T3415D



## Feature:

- 1. Fully digital design, high fidelity, and excellent voice transmission performance
- 2. Built-in 2 x 15W high-quality digital amplifiers, compatible with external speakers, and low power consumption
- 3. Professional DSP audio processing chip, supporting 10-band parametric equalization, delivering high-fidelity CD-quality sound
- 4. Highly reliable design with a long lifespan, mean time between failures (MTBF) > 100,000 hours
- 5. Local wired audio input
- 6. Expandable Bluetooth functionality
- 7. Master volume control
- 8. Automatic standby mode for energy-saving operation when no music signal (including local audio) is present

## **Specification:**

Input/Output	1 local MIC, 1 LINE IN, 1 LINE OUT Output
Speaker Unit	4.5*1, 1*1
Rated Power	2*15W
Input Voltage	DC24V2A
Teaching Microphone	Frequency Response Range: 20Hz-16kHz@±1.5dB
Dynamic Range	85dB
Distortion Rate	≤0.2%
Frequency Selection	Adaptive
Data Rate	2Mbps
Transmitter Power	>10dBm
Sensitivity (1m, 1W)	88±2dB
Maximum SPL (1m)	100±2dB
Frequency Response	100Hz-16kHz
Dimensions	260x200x94mm
Weight	1.8kg