



### Feature:

1. 5-inch TFT true color display with a graphical interface and full touchscreen operation
2. Includes PC programming software, allowing users to edit schedules and change music via a USB flash drive
3. Includes 16GB of internal memory
4. Song title display in Chinese, touchscreen playback, one-click playback, and power management
5. Supports both PC and host manual programming
6. Supports 10 programs, each with 999 programmable timing points
7. Supports lossless and various decoding formats: MP3, MP2, MP1, WMA, APE, FLAC, AC3, DTS, PA, AAC, AMR, ATRC, and WAV
8. Supports automatic music sorting function, no dedicated numbering software required.
9. Supports setting different volume levels for each scheduled music track.
10. Allows setting the external control power to remain on after the task is completed.
11. Features FM radio function with full-band automatic station search, automatic saving, manual quick saving, and multiple modes.
12. Fire protection function: triggers automatic alarm and fire short-circuit output when a short circuit occurs or a DC 12-24V signal is input.
13. 1 local microphone input, 1 line input, and 2 audio outputs.
14. The microphone voice muting level can be set, and the microphone zone power trigger activation can be configured.
15. Equipped with a monitoring function, and the monitoring volume is adjustable.
16. Has a remote upgrade function, and firmware can be upgraded using a TF card.
17. Comes with 6 zones and 2 power channels.
18. Allows setting the advance turn-on time for zones and power.
19. Provides a fast music playback experience; features playback icons and an interface consistent with mainstream playback software such as Kugou.
20. 2U chassis, aluminum alloy panel, and standard body.

### Specification:

Music Storage	SD Card/USB Drive
USB Drive File System	FAT (FAT16), FAT32
Supported SD Card/USB Drive Capacity	128MB-32GB
Supported Playback File Formats	MP3, MP2, MP1, WMA, APE, FLAC, AC3, DTS, PA, AAC, AMR, ATRC, WAV
<b>Audio Signal Electrical Parameters</b>	
Signal-to-Noise Ratio	>90dB
Total Harmonic Distortion	<0.1%
Audio Signal Input	<0.1%
Power Supply Voltage	AC220V±10%

---

Power Consumption	Standby <5W, Full Load <10W
Amplifier Control Power	Single Channel <1000W
Peripheral Control Power	Single Channel <300W
Zone Control Power	Single Channel <300W
Weight	4.7KG
Dimensions	480*320*90MM