



Feature:

1. Standard chassis design, 2U aluminum alloy panel, integrated handle and ear mount design, suitable for cabinet or desktop installation
2. Professional noise gate controls output signal to suppress background music
3. One MP3 master volume knob for unified MP3 volume control, two-band parametric EQ knobs for adjusting bass and treble to enhance sound quality
4. Independent volume knobs for each line input and each microphone channel
5. Ding-dong prelude button automatically plays the prompt tone at maximum volume, with customizable one-touch alarm music
6. MP3 player capable of playing audio from USB flash drives and SD cards up to 32GB, Bluetooth functionality included
7. FM radio capable of receiving radio stations from 88-108MHz
8. 5 audio inputs, including 3 standard line inputs and 2 standard microphone inputs
9. One-channel audio output, loopable to the next amplifier's audio input
10. MIC1 has the highest priority and automatically mutes when a signal is input. Junction FETs perform priority

Specification:

Rated Power	180W
Output	70V, 100V, 4-16Ω, CH1-CH5
Input Sensitivity/Impedance	MIC1, 2, 5mV/600Ω, unbalanced TS input; AUX1, 2, 3: 350mV/10kΩ, unbalanced RCA input
Output Sensitivity/Impedance	1000mV/470Ω, unbalanced TS output
Overload Source EMF	MIC1, 2, 3: >12dB, unbalanced TRS input; AUX1, 2, 3: >20dB, unbalanced RCA input
Tone (Bass)	±10dB @ 100Hz
Tone (Treble)	±10dB @ 10kHz
Frequency Response	50-16kHz (+1dB, -3dB)
Signal-to-Noise Ratio	MIC1, 2: 66dB
AUX1, 2, 3	80dB
Total Harmonic Distortion	0.5% at 1kHz, 1/3 output power
Mute Function	MIC1 prioritizes other channels
Channel Crosstalk Attenuation	≤50dB
Cooling	Front-to-back forced air cooling
Protection	Overheating, overload, and short circuit
Power Supply	AC220V, 60/50Hz
Weight	9kg
Dimensions (W×H×D)	480*355*100mm