



Feature:

1. Single-channel, high-power, pure power amplifier
2. Provides regional power amplification for broadcast systems, suitable for large-area broadcast sound reinforcement
3. 1-channel TRS input, 1-channel TRS cascade output
4. 1-channel RCA input, 1-channel RCA cascade output
5. Front panel with volume control knob
6. Provides robust protection against short circuits, overloads, and overheating
7. Two power output modes: 120V and 240V constant voltage output, and 4-16Ω constant impedance output

Specification:

| | |
|--|--|
| Rated output power | 2000W |
| Speaker output | 240V, 120V, and 4-16Ω |
| Input sensitivity | Input Impedance: 775mV/10kΩ, balanced RCA/TRS jacks |
| Output Sensitivity & Output Source Impedance | 775mV/470Ω, balanced RCA jacks |
| Frequency Response | 50Hz-16kHz (+1dB, -3dB) |
| Signal-to-Noise Ratio | > 90dB |
| Total Harmonic Distortion | 0.5% at 1kHz, 1/3 output power |
| Cooling | Front-to-back forced air cooling, built-in fan activates at 45°C |
| Protection | Overheat, overload, short circuit |
| Power Supply | ~220V, 60/50Hz |
| Dimensions | 482×500×140mm |
| Weight | 28kg |