



### Feature:

1. Single-channel, high-power, pure power amplifier
2. Provides regional power amplification for broadcast systems, suitable for large-area broadcast sound reinforcement
3. 1-channel TRS input, 1-channel TRS cascade output
4. 1-channel RCA input, 1-channel RCA cascade output
5. Front panel with volume control knob
6. Provides robust protection against short circuits, overloads, and overheating
7. Two power output modes: 120V and 240V constant voltage output, and 4-16Ω constant impedance output

### Specification:

|  |  |
|--|--|
| Rated output power                           | 800W   |
| Speaker output                               | 240V, 120V & 4-16Ω   |
| Input sensitivity & output Input Impedance   | 775mV/10kΩ, balanced RCA/TRS jacks                               |
| Output Sensitivity & Output Source Impedance | 775mV/470Ω, balanced RCA jacks                                   |
| Frequency Response                           | 50Hz-16kHz (+1dB, -3dB)  |
| Signal-to-Noise Ratio                        | >90dB  |
| Total Harmonic Distortion                    | 0.5% at 1kHz, 1/3 output power                                   |
| Cooling                                      | Front-to-back forced air cooling, built-in fan activates at 45°C |
| Protection                                   | Overheat, overload, short circuit                                |
| Power Supply                                 | ~220V, 60/50Hz   |
| Dimensions                                   | 482×500×140mm  |
| Weight                                       | 20kg   |