



Feature:

1. High-grade brushed aluminum alloy panel with a stylish appearance and a tamper-resistant, waterproof structure
2. Built-in HD camera; integrated intercom, broadcast, and monitoring functions
3. Built-in high-fidelity, highly directional condenser microphone
4. Built-in 3W monitoring speaker for high speech clarity
5. Supports two-way, full-duplex HD video intercom. Supports full-duplex acoustic echo cancellation and howling suppression (AEC); automatic recording during intercom
6. Supports one short-circuit signal input for connecting to peripherals such as infrared sensors, door sensors, vibration sensors, and emergency buttons to trigger alarms or output linkage
7. Supports one short-circuit signal output for connecting to devices such as alarm lights, door locks, and network cameras. Supports remote DTMF, remote server control commands, or two-way short-circuit input linkage control
8. Supports one AUX input for connecting to external local audio sources
9. Supports one AUX input for connecting to external local audio sources; UXOUT external active speaker output port for speaker amplification (HD sound quality). Automatic broadcast amplification is enabled by default and can be disabled
10. Supports two SIP lines, enabling multiple numbers per device
11. Supports both a help button and an intelligent DSS button, customizable for speed dial, intercom, answer, and hang up
12. Supports one-way ambient monitoring for background sound
13. Automatically transfers unanswered calls to any intercom terminal
14. Supports server-free intercom: LANs can be disconnected from the SIP server. Direct dialing of the server IP address for intercom
15. Supports both POE and external DC12V power supply modes
16. 10/100Mbps Ethernet connection, supporting both LAN and WAN
17. Supports mobile phone dialing for cross-network calls anytime, anywhere, enabling users to page on-site at any time
18. Dust- and waterproof device, capable of 24/7 stable and reliable operation in both low and high temperature environments

Specification:

AUXIN sensitivity	300mV
AUXOUT sensitivity	: 1v
Amplifier Output	2 x 20W 4 ohms
Power Supply	DC24V/PoE
Network Interface	Standard RJ45 Input
Transmission Rate	100Mbps

Supported Protocols	TCP, UDP, IGMP, ICMP, RS485
Power Input	AC100-240V 50Hz/60Hz
Operating Temperature	-20°C to +70°C
Dimensions	115 × 40 × 180mm
Net Weight	0.8kg