



Feature:

1. The waterproof network column speaker terminal is a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by the main control system, it can play background programs, emergency paging, alarm signals, and more from the main control system
2. Compact and elegant appearance, suitable for various decorative spaces
3. Fully digital design, high fidelity, and high voice transmission index
4. Built-in 60W high-quality digital amplifier with low power consumption
5. Highly reliable design with a long service life, mean time between failures (MTBF) > 100,000 hours
6. Overvoltage, overheating, and short-circuit protection features
7. Can receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
8. Can be linked to a camera, allowing real-time viewing of camera feeds through the host software
9. Supports DHCP and static IP network modes; supports AUTO IP function: If no IP address is obtained in DHCP mode, it will automatically switch to a temporary IP address
10. Supports automatic standby mode for energy saving when no music signal (including local audio signal) is present
11. The woofer features PP + rubber rims, a 60mm Y30 external magnet design, and a polypropylene diaphragm for stronger bass
12. The PET diaphragm design and natural silk diaphragm for the tweeter, along with a high-strength plastic bracket, ensure clear, rounded, and bright sound.
13. Aluminum housing, painted in a matte off-white finish, is safe, reliable, rust-resistant, durable, and fade-resistant, with minimal resonance
13. Aluminum material shell, adopting full-aluminum shell material, with sprayed matte off-white finish. It is safe and reliable, rust-proof, durable and non-fading, and the cabinet has low resonance noise
14. Aluminum front grille, made of 1060 pure aluminum, undergoes hardening and anti-oxidation treatment, featuring non-deformability and permanent rust resistance
15. Multi-functional mounting bracket for easy installation
16. Integrated waterproof design, IP66 certified

Specification:

Speaker Units	3 x 4 + 2 x 1
Rated Power	60W
Input Voltage	AC220V 50Hz/60Hz

Sensitivity (1m, 1W)	89±3dB
Frequency Response	140-20kHz
Operating Temperature	-20°C to +60°C
Waterproof Rating	IP66
Dimensions	109 x 102 x 570mm
Net Weight	2.3kg