



### Feature:

1. The waterproof network column speaker terminal is a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by the main control system, it can play background programs, emergency paging, alarm signals, and other signals from the main control system
2. Fully digital design, high fidelity, and high voice transmission index
3. Built-in 15W high-quality digital amplifier with low power consumption
4. Highly reliable design with a long lifespan, mean time between failures (MTBF) > 100,000 hours
5. Can receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
6. Supports automatic standby mode for energy saving when no music signal (including local audio signal) is present
7. Can be linked to a camera, allowing real-time viewing of camera feeds through the host software
8. Features overvoltage, overheating, and short-circuit protection
9. The woofer is constructed of waterproof paper with a fabric edging. 70mm Y30 external magnet design, delivering powerful bass, clear vocals, and crisp treble
10. PET diaphragm design, with a natural silk tweeter diaphragm, ensures a clear, rounded, and bright sound
11. Aluminum housing: 1.6mm all-aluminum construction with a high-grade spray-paint finish. Safe, reliable, rust-resistant, durable, and fade-resistant. Minimizes cabinet resonance and offers a stylish appearance
12. Aluminum front grille: 1060 pure aluminum, hardened and treated for oxidation resistance, ensuring resistance to deformation and rust
13. Front panel: Waterproof ABS plastic

### Specification:

Waterproof rating	IP65
Speaker units	4 x 1 + 2.5 x 1
Rated power	15W
Sensitivity (1m, 1W)	87dB
Frequency response	100-18kHz
Input voltage Power Supply	AC220V 50Hz/60Hz
Operating Temperature	-20°C to +60°C
Dimensions	148 × 101 × 280mm
Net Weight	1.9kg