



Feature:

1. Professional rack-mount industrial control chassis design, featuring an integrated iron and aluminum alloy panel and electroplated steel spray-coated chassis structure, offering superior heat dissipation, interference resistance, dust resistance, and impact resistance
2. High-grade 7U brushed black aluminum alloy panel with chamfered edges and a matte sandblasted finish. A high-gloss finish surrounds the switch buttons and alloy keyboard drawer, highlighting the ultimate in detail and aesthetics
3. 15.6-inch HD touchscreen for easy-to-use touchscreen control
4. Integrated digital matrix industrial keyboard with embedded touchscreen and retractable hidden keyboard and mouse touchpad
5. Built-in high-capacity SSD with vibration and drop resistance, fast read/write speeds, and low power consumption
6. After installing the broadcast system server software, it forms the management and control center of the IP broadcast system, controlling all audio signal sources in the broadcast system. Broadcast zone allocation and terminal information configuration
7. View the real-time status of each broadcast terminal using the electronic map generated by the service software, giving you complete control
8. Standard RJ45 network interface, connects anywhere with an Ethernet port, supports cross-segment and cross-router operation
9. Strong compatibility, compatible with Windows/Linux systems
10. Shock-resistant and anti-interference, with power-activated silent operation, high and low temperature resistance, and adaptable to various environments; supports 24/7 uninterrupted operation
11. Features 2 microphone inputs, 2 line inputs, each with independent volume control, and 1 line output

Specification:

Processor	4th-generation Core i5, dual-core, 4-threaded, 2.7GHz
Display	15.6-inch 4-wire resistive touchscreen, 1366*768 resolution
Memory	DDR3 8GB DIMM slot, expandable to 8GB
Hard Drive	Onboard 128G SSD solid-state drive, mSATA interface
Power Supply	Mean Well fanless professional industrial power supply
Operating System	Supports Windows/Vista/WinXP/Win2000/Linux/UINX
Hard Drive Expansion	1 SATA 2.0 connector, 1 SATA 3.0 connector
Video Interface	1 VGA port, 1 HDMI port
Ethernet Port	1, supports 10/100/1000Mbps
Serial Port	1* RS-232 serial port
USB	2 x 3.0 USB, 4 x 2.0 USB

Input	1 x 3.5mm jack, 1 x 6.35mm jack, 4 x RACline jacks
Power connector	3-position jack
Operating temperature	-10°C to 50°C
Storage temperature	-20°C to 60°C
Relative humidity	5% to 95%, non-condensing
Dimensions	485mm (D) x 300mm (W) x 310mm (H) (excluding feet)
Net weight	11.8kg