



Feature:

- 1. Professional rack-mount industrial control chassis design, featuring an integrated iron and aluminum alloy panel and electroplated steel spray-coated chassis structure, offering superior heat dissipation, interference resistance, dust resistance, and impact resistance
- 2. High-grade 7U brushed black aluminum alloy panel with chamfered edges and a matte sandblasted finish. A high-gloss finish surrounds the switch buttons and alloy keyboard drawer, highlighting the ultimate in detail and aesthetics
- 3. 15.6-inch HD touchscreen for easy-to-use touchscreen control
- 4. Integrated digital matrix industrial keyboard with embedded touchscreen and removable hidden keyboard and mouse touchpad
- 5. Built-in high-capacity SSD with vibration and drop resistance, fast read/write speeds, and low power consumption
- 6. After installing the broadcast system server software, it forms the basis of the IP broadcast system. The management and control center controls all audio source signals, allocates broadcast zones, and configures terminal information for the PA system
- 7. View the real-time status of each PA terminal using an electronic map generated by the service software, ensuring complete control
- 8. Standard RJ45 network interface allows access anywhere with an Ethernet port, supporting cross-segment and cross-router connectivity
- 9. Strong compatibility, compatible with Windows/Linux systems
- 10. Shock-resistant and anti-interference, with power-activated silent operation, high and low temperature resistance, and adaptability to various environments; supports 24/7 uninterrupted operation
- 11. Features two microphone inputs, two line inputs, each with independent volume control, and one line output

Specification:

Processor	4th-generation Core i5, dual-core, four-threaded, 2.7GHz
Display	15.6-inch, 4-wire resistive touchscreen, 1366*768 resolution
Memory	DDR3 8GB DIMM slot, expandable to dual 8GB
Hard Drive	Onboard 128G SSD solid-state drive, mSATA interface
Power Supply	Mean Well fanless professional industrial power supply
Operating System	Supports Windows/Vista/WinXP/Win2000/Linux/UINX
Hard Drive Expansion	1 SATA 2.0 connector, 1 SATA 3.0 connector
Video Interface	1 VGA port, 1 HDMI port
Ethernet Port	1, supports 10/100/1000Mbps
Serial Port	1* RS-232 serial port
USB	2 x 3.0 USB, 4 x 2.0 USB



Webcast Server FP6-M21502

Input	1 x 3.5mm jack, 1 x 6.35mm jack, 4 x RACline jacks	
Power connector	3-position jack	
Operating temperature	-10°C to 50°C	
Storage temperature	-20°C to 60°C	
Relative humidity	5% to 95%, non-condensing	
Dimensions	485mm (D) x 300mm (W) x 310mm (H) (excluding feet)	
Net weight	11.8kg	