



## Feature:

- 1. Professional rack-mount industrial control chassis design, featuring an integrated iron and aluminum alloy panel and electroplated steel spray-coated chassis structure, offering superior heat dissipation, interference resistance, dust resistance, and impact resistance
- 2. High-grade 7U brushed black aluminum alloy panel with chamfered edges and a matte sandblasted finish. A high-gloss finish surrounds the switch buttons and alloy keyboard drawer, highlighting the exquisite detail and aesthetics
- 3. 17.3-inch HD touchscreen for easy-to-use touchscreen control
- 4. Integrated digital matrix industrial keyboard with embedded touchscreen and removable hidden keyboard and mouse touchpad
- 5. Built-in high-capacity SSD with vibration and drop resistance, fast read/write speeds, and low power consumption
- 6. Suitable for installation in broadcast system servers. After installing the software, it becomes the management and control center of the IP broadcast system, controlling all audio source signals, allocating broadcast zones, and configuring terminal information
- 7. The service software generates an electronic map to view the real-time status of each broadcast terminal, giving you complete control
- 8. A standard RJ45 network interface allows access anywhere with an Ethernet port, supporting cross-segment and cross-router connectivity
- 9. Strong compatibility, compatible with Windows/UNIX systems
- 10. Shockproof and anti-interference, with power-activated silent operation, high and low temperature resistance, and adaptability to various environments; it supports 24/7 uninterrupted operation
- 11. Features two microphone inputs, two line inputs, each with independent volume control, and one line output

## **Specification:**

Processor	Core i5 6th Generation, quad-core, quad-thread, 3.3-3.9GHz
Display	17.3-inch 4-wire resistive touchscreen, 1920*1080 resolution
Memory	DDR4, 8GB DIMM slot, expandable up to 32GB
Hard Drive	Onboard 128G SSD, mSATA interface
Power Supply	Mean Well fanless professional industrial power supply
Operating Systems	Supports Windows/Vista/WinXP/Win2000/Linux/UINX
Hard Drive Expansion	1 x SATA 2.0 connector, 1 x SATA 3.0 connector
Video Interface	1 V GA port, 1 HDMI port
Ethernet port	1, supports 10/100/1000 Mbps
Serial port	1 RS-232 serial port





## Webcast Server FP6-M21701

USB	2 3.0 USB ports, 4 2.0 USB ports
Input	1 3.5mm jack, 1 6.35mm jack, 4 RACline ports
Power port	3-position jack
Operating environment	-10°C to 50°C
Storage temperature	-20°C to 60°C
Relative humidity	5% to 95%, non-condensing
Dimensions	485mm (D) x 300mm (W) x 310mm (H) (excluding feet)
Net weight	11.8kg