



Feature:

1. Professional rack-mount industrial control chassis design, featuring an integrated iron and aluminum alloy panel and electroplated steel spray-coated chassis structure, offering superior heat dissipation, interference resistance, dust resistance, and impact resistance
2. High-grade 7U brushed black aluminum alloy panel with chamfered edges and a matte sandblasted finish. A high-gloss finish surrounds the switch buttons and the alloy keyboard drawer, highlighting the exquisite detail and aesthetics
3. 17.3-inch HD touchscreen for easy-to-use touchscreen control
4. Integrated digital matrix industrial keyboard with embedded touchscreen and removable hidden keyboard and mouse touchpad
5. Built-in high-capacity SSD with vibration and drop resistance, fast read/write speeds, and low power consumption
6. After installing the broadcast system server software, it becomes the management and control center of the IP broadcast system, controlling various audio source signals, allocating broadcast zones, and configuring terminal information
7. The service software generates an electronic map to view the real-time status of each broadcast terminal, giving you complete control
8. Standard RJ45 network interface allows access anywhere with an Ethernet port, supporting cross-segment and cross-router connectivity
9. Strong compatibility, compatible with Windows/Linux systems
10. Shockproof and anti-interference, energy-efficient and silent, high and low temperature resistant, adaptable to various environments; supports 24/7 uninterrupted operation
11. Features 2 microphone inputs, 2 line inputs, each with independent volume control, and 1 line output

Specification:

| | |
|----------------------|--|
| Processor | 6th-generation Core i5, quad-core, 4-thread, 3.3-3.9GHz |
| Display | 17.3-inch 4-wire resistive touchscreen, 1920*1080 resolution |
| Memory | DDR4, 16GB DIMM slot, expandable up to 32GB |
| Hard Drive | Onboard 512 GSSD solid-state drive, mSATA interface |
| Power supply | Mean Well fanless professional industrial power supply |
| Operating systems | Supports Windows/Vista/WinXP/Win2000/Linux/UINX |
| Hard drive expansion | 1 SATA 2.0 connector, 1 SATA 3.0 connector |
| Video ports | 1 VGA, 1 HDMI |
| Ethernet port | 1, supports 10/100/1000 Mbps |
| Serial port | 1 RS-232 2 serial ports |
| USB | 2 x 3.0 USB, 4 x 2.0 USB |

| | |
|-----------------------|--|
| Input | 1 x 3.5mm jack, 1 x 6.35mm jack, 4 x RACline ports |
| Power | 3-position jack |
| Operating temperature | -10°C to 50°C |
| Storage temperature | -20°C to 60°C |
| Relative humidity | 5% to 95%, non-condensing |
| Dimensions | 485mm (D) x 300mm (W) x 310mm (H) (excluding feet) |
| Net weight | 11.8kg |