



Feature:

1. Professional desktop video intercom network paging microphone design, durable and sturdy, with a high-grade aluminum alloy panel and an all-metal body
2. High-fidelity gooseneck hose microphone input, with a red indicator automatically lighting up when the microphone is on
3. 10.1 IPS HD display with a 170° wide viewing angle for unobstructed viewing
4. Capacitive touch technology for responsive operation and easy interaction
5. Built-in HD camera with video intercom functionality, enabling intercom between smart paging stations and between smart paging stations and helpdesk terminals. Supports voice prompts, flashing lights, and other features
6. Supports SIP protocol, intercom between VOIP phones, and VOIP paging playback terminals
7. Smart screen saver with configurable screen saver delay for the color display
8. User password and permission management
9. Graphical interface with clear information display and simple and convenient operation
10. Supports zone broadcast, group broadcast, and full zone broadcast
11. Supports TCP, UDP, IGMP, ICMP, and other protocols. Network protocol
12. Built-in professional DSP howling suppression module
13. Emergency one-touch paging button with protective cover to prevent accidental operation
14. MIC automatically shuts off when no audio is input, with a configurable auto-off timer
15. Built-in 3W full-range high-fidelity speaker for monitoring and intercom
16. Supports background speech, with automatic voice priority
17. On-demand control of program sources for zones, groups, and all zones
18. One 3.5mm headphone jack, line input, supports mono or stereo input. Capture and playback functions
19. 1-channel 3.5mm headphone jack with line output, supports external power amplifier
20. Broadcasting function that can continue even when the server is disconnected
21. Network paging is enabled, and the microphone has a manual on/off mute function
22. Standard RJ45 network port, supports LAN and WAN

Specification:

Input Impedance	>10kΩ
Input Sensitivity	0dB (1V)
Frequency	20Hz-20kHz
Output Impedance	<100Ω
Output Amplitude	1.0±0.1V
Frequency Response	20Hz-20kHz
Distortion	≤0.1%

Signal-to-Noise Ratio	≥90dB
MIC Input	Input Sensitivity: 40±mV
Distortion	≤0.5%
Gain Limiting Effective Frequency Range (±3dB)	80Hz-4kHz
Signal-to-Noise Ratio (30kHz Low-Pass)	≥75dB
Network Port	RJ45 (10/100)
Audio Input	3.5mm Headphone Jack
Audio Output	3.5mm Headphone Jack
Interface	USB Port*1
Power Input	DC12V 2A
Operating Temperature	-20°C to +60°C
Dimensions	320×172.8×44.6mm
Net Weight	2.2kg