



### Feature:

1. The Network Power Manager is a power management system based on the TCP/IP transport protocol, capable of connecting to the network for synchronized network and device control
2. High-end 2U aluminum alloy panel and fully metalized chassis design
3. This device features 16 power control channels
4. Each power channel has a maximum output power of 3 kW, for a total power of up to 6000 watts. Each channel can be individually disconnected and connected, or enabled sequentially
5. Equipped with a 4.3-inch touchscreen display that displays the IP address and intuitively displays information such as the output status of each channel
6. Four adjustment buttons and a directional knob allow for setting information such as the IP address, time, and screen off time
7. Control can be implemented via the network broadcast management page
8. Integrated control is possible
9. Advanced protection circuitry ensures stable output current and voltage
10. Each channel can be controlled individually, via the network, or via a timer
11. Features one-touch functionality. Full-on and sequential-on functions
12. Adjustable screen backlight duration and brightness for energy-saving operation
13. Overvoltage and undervoltage indicators, as well as a network indicator
14. 16-way power output port, one short-circuit output port and one short-circuit input port
15. Supports RS485 communication protocol and provides an RS485 interface for communication with third-party systems
16. Supports network protocols such as TCP, UDP, IGMP, and ICMP

### Specification:

Network Port	Standard RJ45 Input
Transmission Rate	100Mbps
Supported Protocols	TCP, UDP, IGMP, ICMP, and RS485
Power Input	AC100-240V, 50Hz/60Hz
Operating Temperature	-20°C to +70°C
Dimensions	482×300×88mm
Net Weight	5.2kg