



Feature:

1. 8-channel IP mixer with a unique top-mount design and high-grade metal panel
2. 7" IPS high-definition display with a 170° wide viewing angle for unobstructed viewing
3. Capacitive touch technology for responsive operation and easy interaction
4. Graphical interface with clear information display for simple and convenient operation
5. Supports zone, group, and global broadcasting
6. On-demand control of zone, group, and global program sources
7. 4 microphone inputs and 4 line inputs
8. 1 3.5mm headphone line input, supporting mono or stereo input, with capture and playback capabilities, and 1 3.5mm headphone mic input
9. 1 3.5mm headphone line output, supporting external power amplifier connection
10. 1 short-circuit input and 1 short-circuit output
11. Supports RS485 communication protocol
12. Broadcasting continues even when the server is disconnected from the network
13. Built-in professional DSP howling suppression module
14. Emergency one-touch paging with a protective cover to prevent accidental operation
15. MIC automatically shuts off when there is no audio input, and the auto-off timer can be set
16. Built-in 3W full-range high-fidelity speaker for monitoring and intercom
17. Supports background speech, with automatic voice priority
18. Standard RJ45 network port, supports LAN and WAN

Specification:

Input sensitivity	300mV
Frequency	20Hz-20kHz
Output amplitude	1.0±0.1V
Frequency Response	20Hz-20kHz
Distortion	≤0.1%
Signal-to-Noise Ratio	≥90dB
MIC Input Sensitivity	40±mV
MIC Distortion	≤0.5%
MIC Gain Limit Effective Frequency Range (±3dB)	80Hz-4kHz
MIC Signal-to-Noise Ratio (30kHz Low Pass)	≥75dB
Product Dimensions	540×345×75mm
Net Weight	5.3kg