



Feature:

1. This network-connected wall-mounted ABS plastic speaker features a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by a master control system, it can play background programs, emergency paging, alarm signals, and more
2. Its curved design offers a stylish and elegant appearance
3. Its fully digital design ensures high fidelity and high voice transmission performance
4. Its built-in 2 x 20W high-quality digital amplifiers support external power amplifiers and low power consumption
5. Its high reliability design offers a long lifespan, with a mean time between failures (MTBF) exceeding 100,000 hours
6. It features overvoltage, overheating, and short-circuit protection
7. It supports 100V network and power outage backup, with a switching time of less than 30ms
8. It supports U-band wireless microphone functionality
9. It supports Bluetooth 5.0
10. It can receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
11. It supports DHCP and static IP network modes; it also supports AUTO IP function: If no IP address is obtained in DHCP mode, the system automatically switches to a temporary IP address
12. Supports automatic standby and energy-saving operation when no music signal (including local audio) is present
13. A bass-and-treble splitter design with a bass-and-treble port ensures exceptional bass and powerful sound
14. The enclosure is made of UV-resistant ABS material for safety and reliability. The thickened housing reduces resonance, making it durable, fade-resistant, and resistant to oxidation
15. The woofer is a PP+rubber-rimmed woofer with an 80mm Y35 external magnet and a polypropylene diaphragm for stronger bass
16. The tweeter is made of a PET diaphragm with a natural silk diaphragm. The high-strength plastic horn ensures clear, rounded, and bright sound
17. The grille is made of 1060 pure aluminum, hardened and treated with an anti-oxidation treatment, making it durable and rust-resistant
18. The mounting bracket is adjustable and can be mounted vertically or tilted
19. One local MIC input, one LINE IN input, and one LINE OUT output

Specification:

Speaker Unit	4.5*1+1*1
Network Interface	RJ45 (10/100M)
Audio Input Sensitivity	300mV

Audio Output	1V
MIC Input Sensitivity	10mV
Amplifier Output Power	2*20W
Input Voltage	AC220-240V 50Hz/60Hz or DC24V 2A
Sensitivity (1m, 1W)	90±2dB
Frequency Response	80-20kHz
Operating Temperature	-20°C to +60°C
Dimensions	176×170×255mm
Net Weight	2.8kg