



Feature:

1. This network-connected wall-mounted wooden speaker features a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by a master control system, it can play background programs, emergency paging, alarm signals, and more
2. Fully digital design, high fidelity, and excellent voice transmission performance
3. Built-in dual 20W high-quality digital amplifiers, compatible with external sub-amps, and low power consumption
4. Highly reliable design with a long lifespan, with a mean time between failures (MTBF) exceeding 100,000 hours
5. Overvoltage, overheating, and short-circuit protection
6. Ability to receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
7. Supports DHCP and static IP network modes; supports AUTO IP, automatically switching to a temporary IP if no IP address is obtained in DHCP mode
8. Supports automatic standby mode for energy saving when no music signal (including local audio) is present
9. The woofer features a waterproof paper plate with a cloth edge and a 70mm Y30 external magnet design, delivering powerful bass, clear vocals, and crisp, bright treble
10. Tweeter Moisture-resistant paper cone design ensures clear, rounded, and bright sound
11. 1 local MIC, 1 line-in input, and 1 line-out output

Specification:

Speaker unit	4.5*1 + 2.5*1
Network interface	RJ45 (10/100M)
Audio input sensitivity	300mV
Audio output	1V
MIC input sensitivity	10mV
Amplifier output power	2*20W
Input voltage	POE 12V/24V
Sensitivity (1m, 1W)	88±2dB
Frequency response	100-18kHz
Operating temperature	-20°C to +60°C
Dimensions	180×140×280mm
Net weight	2.4kg