



Feature:

1. This network-connected wall-mounted wooden speaker features a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by a master control system, it can play background programs, emergency paging, alarm signals, and more
2. Fully digital design, high fidelity, and excellent voice transmission performance
3. Built-in 2 x 30W high-quality digital amplifiers, compatible with external speakers, and low power consumption
4. Highly reliable design with a long lifespan, with a mean time between failures (MTBF) exceeding 100,000 hours
5. Overvoltage, overheating, and short-circuit protection
6. Ability to receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
7. Bluetooth 5.0 support
8. Supports DHCP and static IP network modes; supports AUTO IP, automatically switching to a temporary IP address if no IP address is obtained in DHCP mode
9. Supports automatic standby mode for energy saving when no music signal (including local audio) is present
10. Woofer: PP + rubber-rimmed woofer with 80mm Y35 external magnets and a polypropylene diaphragm for powerful bass
11. Tweeter The PET diaphragm design and natural silk tweeter diaphragm are combined with a high-strength plastic horn for a clear, rounded, and bright sound
12. 1-channel local MIC, 1-channel LINE IN input, and 1-channel LINE OUT output facilitate local expansion

Specification:

| | |
|-------------------------|----------------------------|
| Speaker Unit | 5.5*1 + 1*1 |
| Network Interface | RJ45 (10/100M) |
| Audio Input Sensitivity | 300mV |
| Audio Output | 1V |
| MIC Input Sensitivity | 10mV |
| Amplifier Output Power | 2*30W |
| Input Voltage | DC24V/4A, AC220V 50Hz/60Hz |
| Sensitivity (1m, 1W) | 90±2dB |
| Frequency Response | 80-20kHz |
| Operating Temperature | -20°C to +60°C |
| Product Dimensions | 200 × 152 × 310 mm |
| Net Weight | 3.5 kg |