



Feature:

1. This network-connected wall-mounted wooden speaker features a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by a master control system, it can play background programs, emergency paging, alarm signals, and more
2. Fully digital design, high fidelity, and high voice transmission performance
3. Built-in 2 x 30W high-quality digital amplifiers, compatible with external power amplifiers, and low power consumption
4. Highly reliable design with a long lifespan, mean time between failures (MTBF) > 100,000 hours
5. Overvoltage, overheating, and short-circuit protection
6. Ability to receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
7. Supports U-band wireless microphone functionality
8. Supports Bluetooth 5.0
9. Supports DHCP and static IP network modes; supports AUTO IP function: If no IP address is obtained in DHCP mode, it automatically switches to a temporary IP address
10. Supports automatic standby mode for energy saving when no music signal (including local audio signal) is present
11. Woofer: PP + rubber-rimmed woofer, 80mm Y35 external magnet design, and polypropylene diaphragm for powerful bass
12. Tweeter: PET diaphragm design, natural silk diaphragm. High-strength plastic horn ensures clear, rounded, and bright sound
13. 1 local MIC. 1 line in. and 1 line out. facilitating local expansion

Specification:

Speaker	5.5*1 + 1*1
Network Interface	RJ45 (10/100M)
Audio Input Sensitivity	300mV
Audio Output	1V
MIC Input Sensitivity	10mV
Amplifier Output Power	2*30W
Input Voltage	DC24V/4A AC220V 50Hz/60Hz
Sensitivity (1m, 1W)	90±2dB
Frequency response	80-20kHz
Operating temperature	-20°C to +60°C
Dimensions	200×152×310mm
Net weight	3.6kg