



Feature:

1. This network-connected wall-mounted wooden speaker features a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by a master control system, it can play background programs, emergency paging, alarm signals, and more
2. Fully digital design, high fidelity, and high voice transmission performance
3. Built-in 2 x 30W high-quality digital amplifiers, compatible with external power amplifiers, and low power consumption
4. Highly reliable design with a long lifespan, mean time between failures (MTBF) > 100,000 hours
5. Overvoltage, overheating, and short-circuit protection
6. Ability to receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
7. Supports 100V network and power failure backup, with a switching time of less than 0.03 seconds
8. Supports U-band wireless microphone functionality
9. Supports Bluetooth 5.0
10. Supports DHCP and static IP network modes; supports AUTO IP function: If no IP address is obtained in DHCP mode, it automatically switches to a temporary IP address
11. Supports automatic standby mode for energy saving when no music signal (including local audio signal) is present
12. Woofer: PP + rubber-rimmed woofer, 80mm Y35 external magnet design, and polypropylene diaphragm for stronger bass
13. Tweeter: PET diaphragm design, natural silk diaphragm. High-strength plastic horn ensures clear, rounded, and bright sound
14. 1 local MIC, 1 line in, and 1 line out, facilitating local expansion

Specification:

Speaker	5.5*1 + 1*1
Network Interface	RJ45 (10/100M)
Audio Input Sensitivity	300mV
Audio Output	1V
MIC Input Sensitivity	10mV
Amplifier Output Power	2*30W
Input Voltage	DC24V/4A AC220V 50Hz/60Hz
Sensitivity (1m, 1W)	90±2dB
Frequency response	80-20kHz
Operating temperature	-20°C to +60°C
Dimensions	200×152×310mm
Net weight	4.1kg