



Feature:

1. The IP wall-mounted player terminal is a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by the main control system, it can play background programs, emergency paging, alarm signals, and other signals from the main control system
2. Fully digital design, high fidelity, and high voice transmission index
3. High-grade aluminum alloy overall design
4. Built-in high-quality digital amplifier with low power consumption
5. Features one auxiliary audio input, one auxiliary audio output, and one microphone input
6. Highly reliable design with a long service life, mean time between failures (MTBF) > 100,000 hours
7. Features overvoltage, overheating, and short-circuit protection
8. LED indicators for operating status, network status, and power status
9. Can receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
10. Supports DHCP and static IP network modes; supports the AUTO IP function, which automatically switches to a temporary IP address if an IP address is not obtained in DHCP mode
11. Supports automatic standby mode for energy saving when no music signal (including local audio signal) is present

Specification:

Power Input	POE
Network Interface	RJ45 (10/100M)
Audio Input Sensitivity	300mV
Audio Output	1V
MIC Input Sensitivity	10mV
Amplifier Output Power	2 x 20W
Frequency Response	20Hz-16kHz
Distortion	≤1%
Signal-to-Noise Ratio	≥81dB
Operating Temperature	-20°C to +60°C
Dimensions	155 × 100 × 32mm
Net Weight	0.4kg