



Feature:

1. The IP wall-mounted player terminal is a fully digital analog-to-digital signal processor based on the TCP/IP transmission protocol. Intelligently controlled by the main control system, it can play background programs, emergency paging, alarm signals, and more from the main control system
2. Fully digital design, high fidelity, and excellent voice transmission performance
3. High-grade aluminum alloy construction
4. Built-in high-quality digital amplifier with low power consumption
5. Features one auxiliary audio input, one auxiliary audio output, and one microphone input
6. Highly reliable design with a long lifespan, with a mean time between failures (MTBF) exceeding 100,000 hours
7. Overvoltage, overheating, and short-circuit protection
8. LED indicators for operating status, network status, and power status
9. Can receive emergency paging calls independently of the server, with the volume automatically adjusting to the set value
10. Supports DHCP and static IP network modes; supports AUTO IP, automatically switching to a temporary IP if no IP address is obtained in DHCP mode
11. Supports automatic standby mode for energy saving when no music signal (including local audio) is present

Specification:

Power Input	DC16-24V/2A
Network Interface	RJ45 (10/100M)
Audio Input Sensitivity	300mV
Audio Output	1V
MIC Input Sensitivity	10mV
Amplifier Output Power	2 x 30W
Frequency Response	20Hz-16kHz
Distortion	≤1%
Signal-to-Noise Ratio	≥81dB
Operating Temperature	-20°C to +60°C
Dimensions	155 x 100 x 32mm
Net Weight	0.4kg