



### ► Feature:

1. Built-in high-quality crossover, precisely tuned for accurate sound reproduction.
2. Multi-point hanging design allows both horizontal and vertical installation to meet various mounting requirements.
3. Bottom pole mount enables easy combination with subwoofers.
4. Bottom input terminal design for convenient stage monitor connections.
5. Ergonomic arc-shaped top handle for easy portability.
6. Professional 55° monitor angle design for flexible usage as a stage monitor or full-range speaker.

### ► Specification:

7. LF Driver: 1 × 10" (65mm voice coil, 170mm ferrite magnet)
8. HF Driver: 1 × 1" (34.4mm voice coil, 90mm ferrite magnet)
9. Frequency Response: 65Hz – 20KHz
10. Sensitivity (1W/1M): 97 dB
11. Maximum SPL: 122 dB
12. Rated Power: 350 Watts
13. Peak Power: 700 Watts
14. Nominal Impedance: 8Ω
15. Cabinet Material: Birch plywood
16. Acoustic Design: Arc-shaped front air guide
17. Finish: Eco-friendly black water-based textured paint
18. Grille: 1.2T black painted steel grille (optional dust-proof fabric available)
19. Mounting Options: Multi-point suspension / wall mount / tripod stand
20. Connectors: Parallel 3 × Speakon NL4 + 2 × binding posts + series/parallel switch
21. Dimensions (H × W × D): 510 × 322 × 329 mm
22. Coverage Angle: H 90° × V 60°
23. Net Weight: 16 kg